SPIRAL SE SERIES CONTINUOUS MULTI LAYER STIRRUP BENDING MACHINES







The SPIRAL SE series are the second generation of straightening, bending and cutting machines producing concrete reinforcing stirrups in continuous, multi-layer Spiral form (PATENTED). Coiled Re-bar, High tensile PC-BAR or Wire can be processed and any shape can be produced (i.e. square, rectangular, polygon, circular etc).

The collection table is synchronized with the feeding and bending subassemblies and follows the movement of the produced spirals, enabling accurate spiral production, even for large shapes, dimensions and multiple layers.

The SPIRAL SE series unique advantages include:

- Reduced product costs in comparison to stirrups
- Massive space and labor savings
- Unlimited production flexibility
- Elimination in material waste
- Reduced installation and on-site assembly time
- Better structural protection











SPIRAL SE SERIES



- Excellent straightening and accurate feeding without re-bar marking due to multiple roller feeding.
- The lower rollers of the straightening sub-assemblies are powered, thus creating a positive, precise and evenly distributed feeding
- ✓ Diameter changes can be completed in seconds, thanks to the "Hexagon Shaft Pre-setting System"
- ✓ Adjustable counter-torsion (anti-twist) system always produces flat shapes regardless of re-bar quality, axial twist and bending direction (patent).
- Ergonomic operator interface with user friendly software.
- Remote trouble-shooting via Internet.





| TECHNICAL SPECIFICATIONS | SPIRAL 12 SE 1.0 | SPIRAL 12 SE 1.7 | SPIRAL 16 SE |
|--|------------------------|-------------------------|--|
| Re-bar sizes | Ø 5-12 mm (#4) | Ø 5-12 mm (#4) | Ø 6-16 mm (#5) |
| Wire feeding speed | 100 m/min (330 ft/min) | 100 m/min (330 ft/min) | 90 m/min (300 ft/min) |
| Bending speed | 800 °/sec | 800 °/sec | 800 °/sec |
| Collection table speed | 80 rpm | 40 rpm | 40 rpm |
| Collection table sizes | 1000x1000mm (40"x40") | 1700x1700mm (5′7″x5′7″) | 1700x1700mm (5'7"x5'7") 1200x2500mm (4'x8'2") |
| Bending angle | ± 180° | ± 180° | ± 180° |
| Side accuracy | ± 0,5mm (0.02") | ± 0,5mm (0.02") | ± 0,5mm (0.02") |
| Bending accuracy | ± 0,5° | ± 0,5° | ± 0,5° |
| Max. Number of layers | Up to 60 | Up to 100 | Up to 100 |
| Production output 8h 12mm square spiral | 1000x1000mm 10.5 t | 1000x1000mm 7.5 t | 1000x1000 7.5 t |

SPIRAL SE Re-bar Benders are available with:

- Automatic Spiral discharging crane.
- Spiral bundling table.

For a free video CD and your nearest EUROBEND representative, please, contact:

E U R O B E N D GmbH

ADVANCED TECHNOLOGY PRODUCTS

Allersberger Str. 185, Geb. G-3 D-90461, Nürnberg GERMANY

TEL: +49-911-9498980

TEL: +30-210-8077775

FAX: +30-210-6206567 $\underline{\textbf{WEBSITE:}} \ \underline{\textbf{www.eurobend.com}} \quad \underline{\textbf{e-mail:}} \ \textit{info} \ @eurobend.com$

