

AUTOMATIC ASSEMBLY LINE FOR THE PRODUCTION OF DOWEL BASKETS










- The DBA series of dowel basket assembly line produces all common types and sizes of dowel baskets (PATENTED).
- Extremely versatile design concept, can produce all dowel baskets with minimum changeovers
- Servo driven operation ensures efficiency, reliability and compact machine layout.
- Modular design provides effortless access on all mechanical, electrical and electronic parts.
- Fast & accurate basket size changeovers due to quick set-up systems without extra tooling requirements.



BA SERIES





- Unmatched production rates due to fully • automatic operation, a complete dowel basket produced in less than 90 seconds.
- Side frames are placed into the "dowel sideframe loading station" and are fed automatically through the dowel bar feeder into the welding station of the machine.
- Automatic feeding and positioning of the precut dowel bars, through "dowel bar feeders".
- Unlimited product flexibility, as all common types and shapes of dowel inserts, such as round, rectangular and triangular, plain, epoxy or plastic coated can be used.
- Automatic straightening, cutting, positioning and welding of the shipping wire from coil.
- MIG welding High quality machines, equipped with automatically moving welding guns.
 - Automatic stacking during production flow.
 - Industrial microprocessor control with user-friendly operation and real time online service support.
 - Operator only required to feed the side frames and to supervise the production process.







000000000

	PL DBA
Dowel basket heights	3″ - 12″ (75 - 300 mm)
Dowel basket lengths	3' - 15' (900 – 4600 mm)
Dowel basket leg spacing	12" - 30" (220 – 900 mm)
Dowel bar diameter	¼″ - 1 ½″ (12 - 40 mm)
Dowel bar lengths	15" - 24" (381 – 600 mm)
Shipping wire diameter	0.157" - 0.236" (4 – 6 mm)
Working speed At 18" (450mm) spacing	15' / min. (4,5 m/min)

For a free video CD and your nearest EUROBEND representative, please, contact:

EUROBEND ADVANCED TECHNOLOGY PF	GmbH RODUCTS
Allersberger Str. 185, Geb. G-3 D-90461, Nürnberg GERMANY	GmbH RODUCTS
<u>TEL:</u> +49-911-9498980 <u>TEL:</u> +30-210-8077775	FAX: +30-210-620656



67 WEBSITE: www.eurobend.com e-mail: info@eurobend.com